

Lift&Drive 90IE

Simple but tough





Travel lightly

Don't move around more weight than needed. With optimised weight to capacity ratio, total weight is kept at a minimum.

Cleanability for hygienic work

Easy-to-clean stainless-steel design option, combined with a specially designed mast curtain, contributes to easy cleaning as well as low particle emissions during operation.

Manoeuvrability in tight spaces

Swivel wheels give a very narrow turn radius, making the trolley easy to steer.

When reliability and precision is key

Our unique, spindle-based lifting

lifting and lowering of your load. While saving

time, it also adds safety and reliability, with

minimal maintenance requirements.

system enables speedy and precise

Get the solution to your need

Your optimal solution is determined by the task, the load, the operator, and the work environment. With a wide range of options, and tools, Pronomic can customise a solution that fits your needs and solves your problems.

Ergonomic handgrip for all

Be sure to reduce the strain on muscles and joints during operation by adjusting the handlebars to the optimal working height.

Easy roll with heavy loads

A lifting trolley with low roll resistance makes it easier to move heavy loads, further reducing the strain on your body.

Low build

Fits under pallets, adapted for loading and unloading goods.

Capability when you need it

Lift&Drive 90IE is a simple but capable lifting trolley, wider and longer chassis compared to the ECO range. It's easy to use and easy to stow away, making it ideal for work environments like canteens and kitchens, offices, libraries, or shops – as well as more industrial applications.

The trolley is smooth and stable to use, with a lifting capacity of 90 kg. The handlebars are easily adjusted to suit any operator, and safety features such as overload

protection and safety clutch make the trolley safe to use also by inexperienced operators. Thanks to the motor brake, loads can be kept in an elevated position for longer.

Low roll resistance combined with optimal weight to capacity ratio enables ergonomic and safe lifting without risk of strain. The durable, high-quality build requires only minimal maintenance.

- Reliable high-quality design with minimum
 maintenance needs
- · Compact design to fit any space
- Small footprint when parked
- Easy and safe to use also for inexperienced operators
- Adjustable to suit different operators
- Welded, high polished stainless steel chassis option: easy to clean
- Economic choice for simpler industrial applications

Basic data

Height* (mm)	Min 1433 Max 2183
Length (mm)	764
Width (mm)	550
Net weight (kg)	33
Maximum load including tool (kg)	90
Max lifting speed empty/full (m/min)	5
Safety	CE
Battery	Sealed, valve regulated, lead-acid batteries (VRLA)
Nominal battery voltage	24V DC (12V x 2)
Battery capacity	7.2 Ah
Stainless steel option	Yes



PRONOMIC AB

Box 5504 192 05 Sollentuna Sweden +46 (0) 8 544 706 60 sales@pronomic.com pronomic.com

Smart moves for safe work